

1. CHEMICAL PRODUCT and COMPANY INFORMATION



Bottini Fuel
2785 W. Main Street
Wappingers Falls, NY 12590-1576

EMERGENCY TELEPHONE NUMBER (24 hrs): CHEMTREC (800) 424-9300
COMPANY CONTACT (Business hours): (800) 836-3835

SYNONYMS: #2 Heating Oil; #2 Heating Oil Plus; 2 Oil; Off-road Diesel Fuel; High Sulfur Diesel

#2 Fuel Oil OSHA PEL-TWA: 5 mg/m as mineral oil mist 100 CAS NUMBER: 68476-30-2 ACGIH TLV-TWA: 1997 NOIC - 100 mg/m³, skin, A3 Naphthalene OSHA PEL-TWA: 10 ppm Typically 0.1 CAS NUMBER: 91-20-3 ACGIH TLV-TWA/STEL: 10 / 15 ppm, A4

See Section 16 for abbreviations and acronyms.

2. COMPOSITION and INFORMATION ON INGREDIENTS

CONCENTRATION

A complex combination of hydrocarbons with carbon numbers in the range C9 and higher produced from the distillation of petroleum crude oil.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW CAUTION! OSHA NFPA COMBUSTIBLE LIQUID - SLIGHT TO MODERATE IRRITANT - EFFECTS CENTRAL NERVOUS SYSTEM - HARMFUL OR FATAL IF SWALLOWED

OVERVIEW

Moderate fire hazard. Avoid breathing vapors or mists. May cause dizziness and drowsiness. May cause moderate eye irritation and skin irritation. Long-term, repeated exposure may cause skin cancer. If ingested, do NOT induce vomiting, as this may cause chemical pneumonia fluid in the lungs. EYES Contact with eyes may cause mild irritation. SKIN Practically non-toxic if absorbed following acute (single) exposure. May cause skin irritation with prolonged or repeated contact. Liquid may be absorbed through the skin in toxic amounts if large areas of skin are repeatedly exposed. INGESTION The major health threat of ingestion occurs from the danger of aspiration (breathing) of liquid drops into the lungs, particularly from vomiting. Aspiration may result in chemical pneumonia (fluid in the lungs), severe lung damage, respiratory failure and even death. Ingestion may cause gastrointestinal disturbances, including irritation, nausea, vomiting and diarrhea, and central nervous system (brain) effects similar to alcohol intoxication. In severe cases, tremors, convulsions, loss of consciousness, coma, respiratory arrest, and death may occur. INHALATION Excessive exposure may cause irritations to the nose, throat, lungs and respiratory tract. Central nervous system (brain) effects may include headache, dizziness, loss of balance and coordination, unconsciousness, coma, respiratory failure, and death.

WARNING: the burning of any hydrocarbon as a fuel in an area without adequate ventilation may result in hazardous levels of combustion products, including carbon monoxide, and inadequate oxygen levels, which may cause unconsciousness, suffocation, and death. CHRONIC EFFECTS and CARCINOGENICITY Similar products have produced skin cancer and systemic toxicity in laboratory animals following repeated applications. The significance of these results to human exposures has not been determined - see Section 11 Toxicological Information. MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE Irritation from skin exposure may aggravate existing open wounds, skin disorders, and dermatitis (rash).

4. FIRST AID MEASURES

EYES In case of contact with eyes, immediately flush with clean, low-pressure water for at least 15 min. Hold eyelids open to ensure adequate flushing. Seek medical attention. SKIN Remove contaminated clothing. Wash contaminated areas thoroughly with soap and water or with waterless hand cleanser. Obtain medical attention if irritation or redness develops. INGESTION DO NOT INDUCE VOMITING. Do not give liquids. Obtain immediate medical attention. If spontaneous vomiting occurs, lean victim forward to reduce the risk of aspiration. Monitor for breathing difficulties. Small amounts of material, which enter the mouth, should be rinsed out until the taste is dissipated. INHALATION Remove person to fresh air. If person is not breathing, provide artificial respiration. If necessary, provide additional oxygen once breathing is restored if trained to do so. Seek medical attention immediately.

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES: FLASH POINT: 100.4°F (38 °C) minimum ATSM D-396 AUTOIGNITION POINT: 494 °F (257 °C) OSHA/NFPA FLAMMABILITY CLASS: 2 (COMBUSTIBLE) LOWER EXPLOSIVE LIMIT (%): 0.6 UPPER EXPLOSIVE LIMIT (%): 7.5

FIRE AND EXPLOSION HAZARDS OSHA and NFPA Class 2 COMBUSTIBLE LIQUID (see Section 14 for transportation classification). Vapors may be ignited rapidly when exposed to heat, spark, open flame or other source of ignition. When mixed with air and exposed to an ignition source, flammable vapors can burn in the open or explode in confined spaces. Being heavier than air, vapors may travel long distances to an ignition source and flash back. Runoff to sewer may cause fire or explosion hazard. EXTINGUISHING MEDIA SMALL FIRES: Any extinguisher suitable for Class B fires, dry chemical, CO₂, water spray, fire fighting foam, or Halon. LARGE FIRES: Water spray, fog or fire fighting foam. Water may be ineffective for fighting the fire, but may be used to cool fire-exposed containers. FIRE FIGHTING INSTRUCTIONS Small fires in the incipient (beginning) stage may typically be extinguished using handheld portable fire extinguishers and other fire fighting equipment.

Firefighting activities that may result in potential exposure to high heat, smoke or toxic by-products of combustion should require NIOSH/MSHA- approved pressure-demand self-contained breathing apparatus with full facepiece and full protective clothing. Isolate area around container involved in fire. Cool tanks, shells, and containers exposed to fire and excessive heat with water. For massive fires the use of unmanned hose holders or monitor nozzles may be advantageous to further minimize personnel exposure. Major fires may require withdrawal, allowing the tank to burn. Large storage tank fires typically require specially trained personnel and equipment to extinguish the fire, often including the need for properly applied fire fighting foam. See Section 16 for the NFPA 704 Hazard Rating.

6. ACCIDENTAL RELEASE MEASURES

ACTIVATE FACILITY'S SPCC, SPILL CONTINGENCY OR EMERGENCY RESPONSE PLAN. Evacuate nonessential personnel and remove or secure all ignition sources. Consider wind direction; stay upwind and uphill, if possible. Evaluate the direction of product travel, diking, sewers, etc. to confirm spill areas. Do not touch or walk-through spilled material. Spills may infiltrate subsurface soil and groundwater; professional assistance may be necessary to determine the extent of subsurface impact.



Carefully contain and stop the source of the spill, if safe to do so. Protect bodies of water by diking, absorbents, or absorbent boom, if possible. Do not flush down sewer or drainage systems, unless system is designed and permitted to handle such material. The use of fire fighting foam may be useful in certain situations to reduce vapors. The proper use of water spray may effectively disperse product vapors or the liquid itself, preventing contact with ignition sources or areas/equipment that require protection. Take up with dry earth, sand or other non-combustible, inert oil absorbing materials. Carefully shovel, scoop or sweep up into a waste container with clean, non-sparking tools for reclamation or disposal. Response and clean-up crews must be properly trained and must utilize proper protective equipment (see Section 8). Local and / or Federal notification may be required if this material is released to the environment (see Section 15 for additional information).

7. HANDLING and STORAGE

HANDLING PRECAUTIONS

Handle as a combustible liquid. Keep away from heat, sparks, excessive temperatures and open flame! No smoking or open flame in storage, use or handling areas. Bond and ground containers during product transfer to reduce the possibility of static-initiated fire or explosion. Special slow load procedures for "switch loading" must be followed to avoid the static ignition hazard that can exist when this product is loaded into tanks previously containing low flash point products (such as gasoline) - see API Publication 2003, "Protection Against Ignitions Arising Out Of Static, Lightning and Stray Currents." STORAGE PRECAUTIONS Keep containers closed and clearly labeled. Label all secondary containers that this material is transferred into with the chemical name and associated hazard(s). Use approved vented storage containers. Empty product containers or vessels may contain explosive vapors. Do not pressurize, cut, heat, weld or expose such containers to sources of ignition. Store in a well-ventilated area. Protect containers from damage and vehicular traffic. Post "No Smoking" signs in product storage areas. This storage area should comply with NFPA 30 "Flammable and Combustible Liquid Code". Avoid storage near incompatible materials. The cleaning of tanks previously containing this product should follow API Recommended Practice (RP) 2013 "Cleaning Mobile Tanks In Flammable and Combustible Liquid Service" and API RP 2015 "Cleaning Petroleum Storage Tanks."

WORK/HYGIENIC PRACTICES Emergency eye wash capability should be available in the near proximity to operations presenting a potential splash exposure. Use good personal hygiene practices. Avoid repeated and/or prolonged skin exposure. Wash hands before eating, drinking, smoking, or using toilet facilities. Do not use as a cleaning solvent or harsh abrasive skin cleaners for washing this product from exposed skin areas. Waterless hand cleaners are effective. Promptly remove contaminated clothing and launder before reuse.

Use care when laundering to prevent the formation of flammable vapors which could ignite via washer or dryer. Consider the need to discard contaminated leather shoes and gloves.

8. EXPOSURE CONTROLS and PERSONAL PROTECTION

ENGINEERING CONTROLS Use adequate ventilation to keep vapor concentrations of this product below occupational exposure and flammability limits, particularly in confined spaces. EYE/FACE PROTECTION Safety glasses or goggles are recommended where there is a possibility of splashing or spraying. SKIN PROTECTION Gloves constructed of nitrile, neoprene, or PVC are recommended. Chemical protective clothing such as of E. I. DuPont TyChem®, Saranex® or equivalent recommended based on degree of exposure. Note: The resistance of specific material may vary from product to product as well as with degree of exposure. Consult manufacturer specifications for further information. RESPIRATORY PROTECTION A NIOSH/MSHA-approved air-purifying respirator with organic vapor cartridges or canister may be permissible under certain circumstances where airborne concentrations are or may be expected to exceed exposure limits or for odor or irritation. Protection provided by air-purifying respirators is limited. Refer to OSHA 29 CFR 1910.134, ANSI 288.2-1992, NIOSH Respirator Decision Logic, and the manufacturer for additional guidance on respiratory protection selection. Use a positive pressure, air-supplied respirator if there is a potential for uncontrolled release, exposure levels are not known, in oxygen-deficient atmospheres, or any other circumstance where an air-purifying respirator may not provide adequate protection.



9. PHYSICAL and CHEMICAL PROPERTIES

APPEARANCE

Red or reddish/orange colored (dyed) liquid

ODOR

Mild, petroleum distillate odor

BASIC PHYSICAL PROPERTIES

BOILING RANGE: 340 to 700 °F (171 to 371 °C) VAPOR
PRESSURE: 0.009 psia @ 70 °F (21 °C) VAPOR DENSITY (air =
1): > 1.0 SPECIFIC GRAVITY (H₂O = 1): AP 0.87 PERCENT
VOLATILES: 100 EVAPORATION RATE: Slow; varies with
conditions SOLUBILITY (H₂O): Negligible

10. STABILITY and REACTIVITY **STABILITY:** Stable. Hazardous polymerization will not occur CONDITIONS TO AVOID Avoid high temperatures, open flames, sparks, welding, smoking and other ignition sources. INCOMPATIBLE MATERIALS Keep away from strong acids and oxidizers; Viton ®; Fluorel HAZARDOUS DECOMPOSITION PRODUCTS Carbon monoxide, carbon dioxide and non-combusted hydrocarbons (smoke).

11. TOXICOLOGICAL PROPERTIES

ACUTE TOXICITY Acute Oral LD₅₀ (rat): 14.5 ml/kg Acute Dermal LD₅₀ (rabbit): > 5 ml/kg Guinea Pig Sensitization: negative Primary dermal irritation: moderately irritating (Draize mean irritation score - 3.98 rabbits) Draize eye irritation: mildly irritating (Draize score, 48 hours, unwashed - 2.0 rabbits) CHRONIC EFFECTS AND CARCINOGENICITY Carcinogenic: IARC: NO NTP: NO OSHA: NO ACGIH: 1997 NOIC: A3 Dermal carcinogenicity: positive - mice Studies have shown that similar products produce skin tumors in laboratory animals following repeated applications without washing or removal. The significance of this finding to human exposure has not been determined. Other studies with active skin carcinogens have shown that washing the animal's skin with soap and water between applications reduced tumor formation. This product is similar to Diesel Fuel. IARC classifies whole diesel fuel exhaust particulates as probably carcinogenic to humans (Group 2A) and NIOSH regards it as a potential cause of occupational lung cancer based on animal studies and limited evidence in humans. MUTAGENICITY (genetic effects) Material of similar composition has been positive in a mutagenicity study.

12. ECOLOGICAL INFORMATION

Keep out of sewers, drainage areas and waterways. Report spills and releases, as applicable, under Federal and State regulations (See Section 15 for additional information).

13. DISPOSAL CONSIDERATIONS

Consult federal, state and local waste regulations to determine appropriate disposal options.

14. TRANSPORTATION INFORMATION

PROPER SHIPPING NAME: FUEL OIL, NO. 2 HAZARD CLASS &
PACKING GROUP: 3, PG III DOT IDENTIFICATION NUMBER: NA
1993 DOT SHIPPING LABEL: FLAMMABLE LIQUID
EMERGENCY RESPONSE GUIDEBOOK GUIDE NUMBER: 128

May be reclassified for transportation as a COMBUSTIBLE LIQUID under conditions of DOT 49 CFR 173.120(b)(2).



15. REGULATORY INFORMATION

U.S. FEDERAL, STATE, and LOCAL REGULATORY INFORMATION This product and its constituents listed herein are on the EPA TSCA Inventory. Any spill or uncontrolled release of this product, including any substantial threat of release, may be subject to federal, state and/or local reporting requirements. This product and/or its constituents may also be subject to other regulations at the state and/or local level. Consult those regulations applicable to your facility/operation. CLEAN WATER ACT (OIL SPILLS) Any spill or release of this product to "navigable waters" (essentially any surface water, including certain wetlands) or adjoining shorelines sufficient to cause a visible sheen or deposit of a sludge or emulsion must be reported immediately to the National Response Center (1-800-424-8802) or, if not practical, the U.S. Coast Guard with follow-up to the National Response Center, as required by U.S. Federal Law. Also contact appropriate state and local regulatory agencies as required. EPA NOTIFICATION (OIL SPILLS) If there is a discharge of more than 1,000-gallons of oil into or upon navigable waters of the United States, or if it is the second spill event of 42 gallons or more of oil into water within a twelve (12) month period, a written report must be submitted to the Regional Administrator of the EPA within sixty days of the event.

RCRA Information If disposed, this product would be considered a hazardous waste under RCRA with an EPA waste code of D001 for the characteristic of ignitibility. CERCLA SECTION 103 and SARA SECTION 304 (RELEASE TO THE ENVIRONMENT) The CERCLA definition of hazardous substances contains a "petroleum exclusion" clause, which exempts crude oil, refined, and unrefined petroleum products and any indigenous components of such. However, other federal reporting requirements (e.g., SARA Section 304 as well as the Clean Water Act if the spill occurs on navigable waters) may still

apply.

SARA SECTION 311/312 - HAZARD CLASSES

ACUTE HEALTH	CHRONIC HEALTH	FIRE	SUDDEN RELEASE OF PRESSURE	REACTIVE
X	X	X	--	--

SARA SECTION 313 - SUPPLIER NOTIFICATION

This product does not contain toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act (EPCRA) of 1986 and of 40 CFR 372. However, Polycyclic Aromatic Compounds (PACs) are coincidentally manufactured from the combustion of various fuel oils and other petroleum products. Under SARA Section 313, the de minimis exemption has been eliminated for PACs and other listed persistent bio-accumulative and toxic chemicals (PBTs). Refer to EPA guidance for additional reporting information.

CANADIAN REGULATORY INFORMATION (WHMIS) Class B, Division 3(Combustible Liquid); Class D, Division 2, Subdivision B (Toxic by other means)

16. OTHER INFORMATION

NFPA@ HAZARD RATING HEALTH: 0 Negligible
FIRE: 2 Moderate REACTIVITY: 0 Negligible

HMIS® HAZARD RATING HEALTH: 1 * Slight FIRE:
2 Moderate REACTIVITY: 0 Negligible

* Chronic

ABBREVIATIONS:

AP = Approximately < = Less than > = Greater than N/A = Not Applicable N/D = Not Determined ppm = parts per million



ACRONYMS:

ACGIH	American Conference of Governmental Industrial Hygienists	OSHA	U.S. Occupational Safety & Health Administration
API	American Petroleum Institute	PEL	Permissible Exposure Limit (OSHA)
AIHA	American Industrial Hygiene Association	RCRA	Resource Conservation and Recovery Act
CERCLA	Comprehensive Emergency Response, Compensation, and Liability Act	REL	Recommended Exposure Limit (NIOSH)
ANSI	American National Standards Institute	SARA	Superfund Amendments and Reauthorization Act of 1986 Title III
DOT	U.S. Department of Transportation	SCBA	Self-Contained Breathing Apparatus
EPA	U.S. Environmental Protection Agency	SPCC	Spill Prevention, Control, and Countermeasures
HMS	Hazardous Materials Information System	STEL	Short-Term Exposure Limit (generally 15 minutes)
IARC	International Agency For Research On Cancer	TLV	Threshold Limit Value (ACGIH)
MSHA	Mine Safety and Health Administration	TSCA	Toxic Substances Control Act
NFPA	National Fire Protection Association	TWA	Time Weighted Average (8 hr.)
NIOSH	National Institute of Occupational Safety and Health	WEEL	Workplace Environmental Exposure Level (AIHA)
NOIC	Notice of Intended Change	WHMIS	Canadian Workplace Hazardous
NTP	National Toxicology Program		

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES Information presented herein has been compiled from sources considered to be dependable, and is accurate and reliable to the best of our knowledge and belief, but is not guaranteed to be so. Since conditions of use are beyond our control, we make no warranties, expressed or implied, except those that may be contained in our written contract of sale or acknowledgment.

Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material, even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in their use of the material.