



MATERIAL SAFETY DATA SHEET

Gasoline, Unleaded Plus

1. CHEMICAL PRODUCT and COMPANY INFORMATION

EMERGENCY TELEPHONE NUMBER (24 hrs): CHEMTREC (800) 424-9300
COMPANY CONTACT (Business hours): (800) 836-3835

Bottini Fuel
2785 W. Main Street
Wappingers Falls, NY 12590-1576



SYNONYMS: 89 Octane Conventional (Oxygenated and Non-oxygenated) and Reformulated (RFG) Unleaded Plus Gasoline

See Section 16 for abbreviations and acronyms.

2. COMPOSITION and INFORMATION ON INGREDIENTS *

| NAME* | EXPOSURE LIMITS | PERCENT BY WEIGHT | CONCENTRATION INGREDIENT |
|------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|-------------------|---------------------------------------------------------|
| Gasoline CAS NUMBER: 8006-61-9 | OSHA PEL-TWA/STEL: None established ACGIH TLV-TWA/STEL:300/ 500 ppm, A3 | | 100 |
| Benzene CAS NUMBER: 71-43-2 | OSHA PEL-TWA/STEL: 1/5 ppm ACGIH TLV-TWA:0.5/ 2.5 ppm, AI, skin US Coast Guard: same as OSHA | | 0.1 to 4.9 0.1 to 1.3* *for reformulated gasoline |
| Methyl-tertiary butyl ether (MTBE) CAS NUMBER: 1634-044 | OSHA PEL-TWA/STEL: None established ACGIH TLV-TWA: 40 ppm, A3 | | 0 to 15.0 |
| Tertiary-amyl methyl ether (TAME) CAS NUMBER: 994-05-8 | None established | | 0 to 17.2 |
| Toluene CAS NUMBER: 108-88-3 | OSHA PEL-TWA/Ceiling: 200/ 300 ppm OSHA PEL-Peak: 500 ppm (10 mm.) ACGIH TLV-TWA: 50 ppm, A4 (skin) | | 1-15 |
| Xylene, mixed isomers CAS NUMBER: 1330-20-7 | OSHA PEL-TWA: 100 ppm ACGIH TLV-TWA/STEL: 100/ 150 ppm, A4 | | 1-15 |

A complex blend of petroleum-derived normal and branched-chain alkane, cycloalkane, alkene, and aromatic hydrocarbons. Butane is often added to increase volatility, especially in winter. May contain antioxidant and multifunctional additives. Oxygenated and reformulated gasoline will have legally-required amounts of oxygenates (MTBE and/or TAME). *Also see Section 15 for list of SARA Section 313 toxic chemicals and their exposure limits.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW DANGER! EXTREMELY FLAMMABLE --EYE AND MUCOUS MEMBRANE IRRITANT-- EFFECTS CENTRAL NERVOUS SYSTEM -- HARMFUL OR FATAL IF SWALLOWED -- ASPIRATION HAZARD

High fire hazard. Keep away from heat, spark, open flame, and other ignition sources.

If ingested, do NOT induce vomiting, as this may cause chemical pneumonia (fluid in the lungs). Contact may cause eye, skin and mucous membrane irritation. Harmful if absorbed through the skin. Avoid prolonged breathing of vapors or mists. Inhalation may cause irritation, anesthetic effects (dizziness, nausea, headache, intoxication), and respiratory system effects. Long-term exposure may cause effects to specific organs, such as to the liver, kidneys, blood, nervous system, and skin. Contains benzene, which can cause blood disease, including anemia and leukemia.

EYES Moderate irritant. Contact with liquid or vapor may cause irritation.

SKIN Practically non-toxic if absorbed following acute (single) exposure. May cause skin irritation with prolonged or repeated contact. Liquid may be absorbed through the skin in toxic amounts if large areas of skin are exposed repeatedly.

INGESTION The major health threat of ingestion occurs from the danger of aspiration (breathing) of liquid drops into the lungs, particularly from vomiting. Aspiration may result in chemical pneumonia (fluid in the lungs), severe lung damage, respiratory failure and even death.

Ingestion may cause gastrointestinal disturbances, including irritation, nausea, vomiting and diarrhea, and central nervous system (brain) effects similar to alcohol intoxication. In severe cases, tremors, convulsions, loss of consciousness, coma, respiratory arrest, and death may occur.

INHALATION Excessive exposure may cause irritations to the nose, throat, lungs and respiratory tract. Central nervous system (brain) effects may include headache, dizziness, loss of balance and coordination, unconsciousness, coma, respiratory failure, and death.

WARNING: the burning of any hydrocarbon as a fuel in an area without adequate ventilation may result in hazardous levels of combustion products, including carbon monoxide, and inadequate oxygen levels, which may cause unconsciousness, suffocation, and death.

CHRONIC EFFECTS and CARCINOGENICITY Contains benzene, a regulated human carcinogen. Benzene has the potential to cause anemia and other blood diseases, including leukemia, after repeated and prolonged exposure. Exposure to light hydrocarbons in the same boiling range as this product has been associated in animal studies with systemic toxicity. See also Section 11 - Toxicological Information.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE Irritation from skin exposure may aggravate existing open wounds, skin disorders, and dermatitis (rash). Chronic respiratory disease, liver or kidney dysfunction, or pre-existing central nervous system disorders may be aggravated by exposure.

4. FIRST AID MEASURES

EYES In case of contact with eyes, immediately flush with clean, low-pressure water for at least 15 mm. Hold Eyelids open to ensure adequate flushing. Seek medical attention.

SKIN Remove contaminated clothing. Wash contaminated areas thoroughly with soap and water or waterless hand cleanser. Obtain medical attention if irritation or redness develops.

INGESTION DO NOT INDUCE VOMITING. Do not give liquids. Obtain immediate medical attention. If spontaneous vomiting occurs, lean victim forward to reduce the risk of aspiration. Small amounts of material which enter the mouth should be rinsed out until the taste is dissipated.

INHALATION Remove person to fresh air. If person is not breathing, ensure an open airway and provide artificial respiration. If necessary, provide additional oxygen once breathing is restored if trained to do so. Seek medical attention immediately.

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES:

FLASH POINT: -45 °F (-43 °C) AUTOIGNITION TEMPERATURE: highly variable; >530 °F (>280 °C) OSHA/NFPA FLAMMABILITY CLASS: 1A (flammable liquid) LOWER EXPLOSIVE LIMIT (%): 1.4% UPPER EXPLOSIVE LIMIT (%): 7.6%

FIRE AND EXPLOSION HAZARDS Vapors may be ignited rapidly when exposed to heat, spark, open flame or other source of ignition. Flowing product may be ignited by self-generated static electricity. When mixed with air and exposed to an ignition source, flammable vapors can burn in the open or explode in confined spaces. Being heavier than air, vapors may travel long distances to an ignition source and flash back. Runoff to sewer may cause fire or explosion hazard.

EXTINGUISHING MEDIA SMALL FIRES: Any extinguisher suitable for Class B fires, dry chemical, CO₂, water spray, fire fighting foam, or Halon.

LARGE FIRES: Water spray, fog or fire fighting foam. Water may be ineffective for fighting the fire, but may be used to cool fire-exposed containers.

During certain times of the year and/or in certain geographical locations, gasoline may contain MTBE and/or TAME. Firefighting foam suitable for polar solvents is recommended for fuel with greater than 10% oxygenate concentration - refer to NFPA 11 'Low Expansion Foam -1994 Edition.'

FIRE FIGHTING INSTRUCTIONS Small fires in the incipient (beginning) stage may typically be extinguished using handheld portable fire extinguishers and other fire fighting equipment.

Firefighting activities that may result in potential exposure to high heat, smoke or toxic by-products of combustion should require NIOSH/MSHA- approved pressure-demand self-contained breathing apparatus with full face piece and full protective clothing. Isolate area around container involved in fire. Cool tanks, shells, and containers exposed to fire and excessive heat with water. For massive fires the use of unmanned hose holders or monitor nozzles may be advantageous to further minimize personnel exposure. Major fires may require withdrawal, allowing the tank to burn. Large storage tank fires typically require specially trained personnel and equipment to extinguish the fire, often including the need for properly applied fire fighting foam. *See Section 16 for the NFPA 704 Hazard Rating.*

6. ACCIDENTAL RELEASE MEASURES –

ACTIVATE FACILITY SPILL CONTINGENCY or EMERGENCY PLAN.

Evacuate nonessential personnel and remove or secure all ignition sources. Consider wind direction; stay upwind and uphill, if possible. Evaluate the direction of product travel, diking, sewers, etc. to confirm spill areas. Spills may infiltrate subsurface soil and groundwater; professional assistance may be necessary to determine the extent of subsurface impact. Carefully contain and stop the source of the spill, if safe to do so. Protect bodies of water by diking absorbents, or absorbent boom, if possible. Do not flush down sewer or drainage systems, unless system is designed and permitted to handle such material. The use of fire fighting foam may be useful in certain situations to reduce vapors. The proper use of water spray may effectively disperse product vapors or the liquid itself, preventing contact with ignition sources or areas/equipment that require protection. Take up with sand or other oil absorbing materials. Carefully shovel, scoop or sweep up into a waste container for reclamation or disposal - caution, flammable vapors may accumulate in closed containers. A waste characterization should be made on the accumulated material following the standards set forth in 40 CFR 261. Response and cleanup crews must be properly trained and must utilize proper protective equipment.

7. HANDLING and STORAGE

HANDLING PRECAUTIONS x USE ONLY AS A MOTOR FUEL x DO NOT SIPHON BY MOUTH

Handle as a flammable liquid. Keep away from heat, sparks, and open flame! Electrical equipment should be approved for classified area. Bond and ground containers during product transfer to reduce the possibility of static-initiated fire or explosion.

Special slow load procedures for “switch loading” must be followed to avoid the static ignition hazard that can exist when higher flash point material (such as fuel oil) is loaded into tanks previously containing low flash point products (such as this product) - see API Publication 2003, “Protection Against Ignitions Arising Out Of Static, Lightning and Stray Currents.

STORAGE PRECAUTIONS Keep away from flame, sparks, excessive temperatures and open flame. Use approved vented containers. Keep containers closed and clearly labeled. Empty product containers or vessels may contain explosive vapors. Do not pressurize, cut, heat, weld or expose such containers to sources of ignition. Store in a well-ventilated area. This storage area should comply with NFPA 30 “Flammable and Combustible Liquid Code”. Avoid storage near incompatible materials. The cleaning of tanks previously containing this product should follow API Recommended Practice (RP) 2013 “Cleaning Mobile Tanks In Flammable and Combustible Liquid Service” and API RP 2015 “Cleaning Petroleum Storage Tanks”.

WORK/HYGIENIC PRACTICES Emergency eye wash capability should be available in the near proximity to operations presenting a potential splash exposure. Use good personal hygiene practices. Avoid repeated and/or prolonged skin exposure. Wash hands before eating, drinking, smoking, or using toilet facilities. Do not use as a cleaning solvent on the skin. Do not use solvents or harsh abrasive skin cleaners for washing this product from exposed skin areas. Waterless hand cleaners are effective. Promptly remove contaminated clothing and launder before reuse. Use care when laundering to prevent the formation of flammable vapors which could ignite via washer or dryer. Consider the need to discard contaminated leather shoes and gloves.

8. EXPOSURE CONTROLS and PERSONAL PROTECTION

ENGINEERING CONTROLS Use adequate ventilation to keep vapor concentrations of this product below occupational exposure and Flammability limits, particularly in confined spaces.

EYE/FACE PROTECTION Safety glasses or goggles are recommended where there is a possibility of splashing or spraying.

SKIN PROTECTION Gloves constructed of nitrile or neoprene are recommended. Chemical protective clothing such as of E.I. DuPont Tychem ®, Barricade®, or equivalent recommended based on degree of exposure.

Note: The resistance of specific material may vary from product to product as well as with degree of exposure. Consult manufacturer specifications for further information.

RESPIRATORY PROTECTION A NIOSH/MSHA-approved air-purifying respirator with organic vapor cartridges or canister may be permissible under certain circumstances where airborne concentrations are or may be expected to exceed exposure limits or for odor or irritation. Protection provided by air-purifying respirators is limited. Refer to OSHA 29 CFR 1910.134, ANSI Z88.2-1992, NIOSH Respirator Decision Logic, and the manufacturer for additional guidance on respiratory protection selection and limitations. Use a positive pressure, air-supplied respirator if there is a potential for uncontrolled release, exposure levels are not known, in oxygen-deficient atmospheres, or any other circumstance where an air-purifying respirator may not provide adequate protection.

9. PHYSICAL and CHEMICAL PROPERTIES

APPEARANCE A clear, water-like liquid

ODOR A strong, characteristic aromatic hydrocarbon odor. Oxygenated gasoline with MTBE and/or TAME may have a sweet, ether-like odor and is detectable at a lower concentration than non-oxygenated gasoline.

ODOR THRESHOLD Odor Detection Odor Recognition Non-oxygenated gasoline: 0.5-0.6 ppm 0.8-1.1 ppm Gasoline with 15% MTBE: 0.2-0.3 ppm
0.4-0.7 ppm Gasoline with 15% TAME: 0.1 ppm 0.2 ppm

BASIC PHYSICAL PROPERTIES

BOILING RANGE: 85 to 437 °F (39 to 200 °C)

VAPOR PRESSURE: 7-15 RVP @ 100 °F (38 °C) (275-475mm Hg @ 68 °F (20 °C)

VAPOR DENSITY (air = 1): AP 3 to 4

SPECIFIC GRAVITY (H₂O = 1): 0.76

EVAPORATION RATE: 10-11 (n-butyl acetate = 1)

PERCENT VOLATILES: 100%

SOLUBILITY (H₂O): Non-oxygenated gasoline-negligible (<0.1% @ 77 °F). Gasoline with 15% MTBE - slight (0.1 - 3% @ 77 °F)

10. STABILITY and REACTIVITY

STABILITY: Stable. Hazardous polymerization will not occur.

CONDITIONS TO AVOID Avoid high temperatures, open flames, sparks, welding, smoking and other ignition sources

INCOMPATIBLE MATERIALS

Keep away from strong oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS Carbon monoxide, carbon dioxide and non-combusted hydrocarbons (smoke). Contact with nitric and sulfuric acids will form nitroresols that can decompose violently.

11. TOXICOLOGICAL PROPERTIES

ACUTE TOXICITY Acute Dermal LD50 (rabbits): >5 ml/kg Acute Oral LD50 (rat): 18.75 ml/kg

Primary dermal irritation (rabbits): slightly irritating Draize eye irritation (rabbits): non-irritating

Guinea pig sensitization: negative

CHRONIC EFFECTS AND CARCINOGENICITY Carcinogenicity: OSHA: NO IARC: YES - 2B NTP: NO

ACGIH: YES (A3) IARC has determined that gasoline and gasoline exhaust are possibly carcinogenic in humans.

Inhalation exposure to completely vaporized unleaded gasoline caused kidney cancers in male rats and liver tumors in female mice. The

U.S. EPA has determined that the male kidney tumors are species-specific and are irrelevant for human health risk assessment. The significance of the tumors seen in female mice is not known. Exposure to light hydrocarbons in the same boiling range as this product has been associated in animal studies with effects to the central and peripheral nervous systems, liver, and kidneys. The significance of these animal models to predict similar human response to gasoline is uncertain. This product contains benzene. Human health studies indicate that prolonged and/or repeated overexposure to benzene may cause damage to the blood-forming system (particularly bone marrow), and serious blood disorders such as aplastic anemia and leukemia. The NTP, ARC, OSHA and ACGIH list benzene as a human carcinogen.



This product may contain methyl tertiary butyl ether (MTBE): animal and human health effects studies indicate that MTBE may cause eye, skin, and respiratory tract irritation, central nervous system depression and neurotoxicity. MTBE is classified as an animal carcinogen (A3) by the ACGIH.

12. ECOLOGICAL INFORMATION

Keep out of sewers, drainage areas and waterways. Report spills and releases, as applicable, under Federal and State regulations.

13. DISPOSAL CONSIDERATIONS

Consult federal, state and local waste regulations to determine appropriate disposal options.

14. TRANSPORTATION INFORMATION

DOT PROPER SHIPPING NAME: DOT

HAZARD CLASS and PACKING GROUP:

Gasoline 3, PG II UN 1203 FLAMMABLE LIQUID

DOT IDENTIFICATION NUMBER: DOT

SHIPPING LABEL:

15. REGULATORY INFORMATION

U.S. FEDERAL, STATE, and LOCAL REGULATORY INFORMATION This product and its constituents listed herein are on the EPA TSCA Inventory. Any spill or uncontrolled release of this product, including any substantial threat of release, may be subject to federal, state and/or local reporting requirements. This product and/or its constituents may also be subject to other federal, state, or local regulations; consult those regulations applicable to your facility/operation.

CLEAN WATER ACT (OIL SPILLS) Any spill or release of this product to "navigable waters" (essentially any surface water, including certain wetlands) or adjoining shorelines sufficient to cause a visible sheen or deposit of a sludge or emulsion must be reported immediately to the National Response Center (1-800-424-8802) or, if not practical, the U.S. Coast Guard with follow-up to the National Response Center, as required by U.S. Federal Law. Also contact appropriate state and local regulatory agencies as required.

CERCLA SECTION 103 and SARA SECTION 304 (RELEASE TO THE ENVIRONMENT) The CERCLA definition of hazardous substances contains a "petroleum exclusion" clause which exempts crude oil, refined, and unrefined petroleum products and any indigenous components of such. However, other federal reporting requirements (e.g., SARA Section 304 as well as the Clean Water Act if the spill occurs on navigable waters) may still apply.

RCRA INFORMATION If disposed, this product would be considered a hazardous waste under RCRA with the EPA waste codes of D001 for the characteristic of ignitibility, and D018 for Benzene

SARA SECTION 311-312- HAZARD CLASSES ACUTE HEALTH CHRONIC HEALTH FIRE SUDDEN
RELEASE OF PRESSURE REACTIVE X X X -- -

This material is subject to the reporting requirements of Section 311-312 of the Emergency Planning and Community Right to Know Act (EPCRA) if stored at quantities in excess of 10,000 pounds at any one time.

SARA SECTION 313- SUPPLIER NOTIFICATION This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act (EPCRA) of 1986 and of 40 CFR 372.

MATERIAL SAFETY DATA SHEET

Gasoline, Unleaded Plus

CONCENTRATION INGREDIENT NAME (CAS NUMBER) WT.

PERCENT EXPOSURE LIMITS

Benzene (71-43-2) 0.1 to 4.9 See Section 2 Benzene (71-43-2) for reformulated gasoline 0.1 to 1.3* See Section 2

Ethyl benzene (100-41-4) <3 OSHA PEL-TWA: 100 ppm

ACGIH TLV-TWA/STEL: 100/125 ppm n-Hexane (110-54-

3) 0.5 to 4 OSHA PEL-TWA: 500 ppm

ACGIH TLV-TWA: 50 ppm Methyl-tertiary

butyl ether (MTBE) (1634-04-4) 0 to 15.0 See Section 2 Toluene (108-88-3) 1 to 15 See Section 2 1,2,4-

Trimethylbenzene (95-63-6) <6 OSHA PEL-TWA/STEL: 25 ppm

ACGIH TLV-TWA/STEL: 25 ppm Xylene, mixed

isomers (1330-20-7) 1 to 15 See Section 2

CANADIAN REGULATORY INFORMATION (WHMIS) Class B, Division 2 (Flammable Liquid)
Class D, Division 2A (Very toxic by other means) and Class D, Division 2B (Toxic by other means)

16. OTHER INFORMATION

NFPA® HAZARD RATING HEALTH: 1 Slight FIRE: 3
Serious REACTIVITY: 0 Minimal

HMIS® HAZARD RATING HEALTH: 1* Slight
FIRE: 3 Serious REACTIVITY: 0 Minimal
*CHRONIC

ABBREVIATIONS: AP = Approximately <= Less than >= Greater
than N/A = Not Applicable N/D = Not Determined ppm= parts per
million

ACRONYMS:

| | | | |
|--------|-------------------------------------------------------------------|------|----------------------------------------------------------------|
| ACGIH | American Conference of Governmental Industrial Hygienists | OSHA | U.S. Occupational Safety & Health Administration |
| API | American Petroleum Institute | PEL | Permissible Exposure Limit (OSHA) |
| AIHA | American Industrial Hygiene Association | RCRA | Resource Conservation and Recovery Act |
| CERCLA | Comprehensive Emergency Response, Compensation, and Liability Act | REL | Recommended Exposure Limit (NIOSH) |
| ANSI | American National Standards Institute | SARA | Superfund Amendments and Reauthorization Act of 1986 Title III |
| DOT | U.S. Department of Transportation | SCBA | Self-Contained Breathing Apparatus |
| EPA | U.S. Environmental Protection Agency | SPCC | Spill Prevention, Control, and Countermeasures |
| HMIS | Hazardous Materials Information System | STEL | Short-Term Exposure Limit (generally 15 minutes) |
| IARC | International Agency For Research On Cancer | TLV | Threshold Limit Value (ACGIH) |
| MSHA | Mine Safety and Health Administration | TSCA | Toxic Substances Control Act |
| NFPA | National Fire Protection Association | TWA | Time Weighted Average (8 hr.) |
| NIOSH | National Institute of Occupational Safety and Health | | |
| NOIC | Notice of Intended Change | WEEL | Workplace Environmental Exposure Level (AIHA) |



DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES Information presented herein has been compiled from sources considered to be dependable, and is accurate and reliable to the best of our knowledge and belief, but is not guaranteed to be so. Since conditions of use are beyond our control, we make no warranties, expressed or implied, except those that may be contained in our written contract of sale or acknowledgment. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material, even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in their use of the material.